## पावर ग्रिड कारपोरेशन ऑफ इंडिया लिमिटेड

(भारत सरकार का उद्यम)

## POWER GRID CORPORATION OF INDIA LIMITED

(A Government of India Enterprise)



केन्द्रीय कार्यालय : "सौदामिनी" प्लॉट सं. २. सैक्टर-२९, गुडगाँव-122 001, हरियाणा फोन : 2571700 - 719, फैक्स : 2571760, 2571761 तार 'नेटग्रिड' Corporate Office : "Saudamini" Plot No. 2, Sector-29, Gurgaon-122 001. Haryana

Tel.: 2571700 - 719, Fax: 2571760, 2571761 Gram: 'NATGRID'

संदर्भ संख्या/क्ट्रि/ट्रिंग्रेशिया/2015/96

Date: 28<sup>th</sup> July, 2015

Shri Ikbal Samad A-1, Opposite ESI Hospital Hatwada Road, Jaipur Rajasthan-302006

Sub: Information under Right to Information Act, 2005.

Dear Mr. Samad,

This has reference to your RTI request dated 25<sup>th</sup> June 2015 (received on 6<sup>th</sup> July, 2015) seeking information under RTI Act, 2005.

The information sought is attached at Annex-I.

Details of Appellate Authority at Corporate Centre, Gurgaon, under RTI Act, 2005 is as below:

Shri B. Mishra
Executive Director (CP & IT) & Appellate Authority
Corporate Centre, Power Grid Corporation of India Limited
"Saudamini", Plot No. 2, Sector-29
Gurgaon – 122007, Haryana

Thanking You,

भवदीय,

(सुधीर मित्तल) 2

महाप्रबंधक(के.आ.)एवं के.लो.स्.अधिकारी

## Information sought by Sh. Ikbal Samad, Jaipur, Rajasthan under the RTI Act, 2005.

The information sought by the requester is general in nature and do not pertain specifically to any transmission line of POWERGRID. This information has already been provided to him under his RTI request Reg.No. POWER/R/2015/60193 dtd. 22/04/2015. However, same is being provided again in the requested format given below:

Sr. No.	HT POWER LINE	RIGHT OF WAY (ROW) (IN MTR)	EHV (IN MTR)	GROUND CLEARANCE (IN MTR)
1	2	3	4	5
1.	765 kV S/C (DELTA CONFIGURATION)	64	*	15 #
2.	765 kV S/C (HORIZONTAL CONFIGURATION)	85	*	15 #
3.	765 kV D/C (VERTICAL CONFIGURATION)	67	*	15 #

<sup>\*</sup> It is not clear what information is required.

<sup>#</sup> Minimum ground clearance from lowest conductor is governed by Central Electricity Authority Regulations for "Measures relating to Safety and Electric Supply, 2010". For 765 kV lines, ground clearance is generally kept as 15.0m.